



PN 20 PP-R PIPE

Specification(mm):

Φ20x2.8	Φ63x8.6
Φ25x3.5	Φ75x10.1
Φ32x4.4	Φ90x12.3
Φ40x5.5	Φ110x15.1
Φ50x6.9	Φ125x17.4

PN25 PP-R PIPE

Specification(mm):

Φ20x3.4	Φ63x10.5
Φ25x4.2	Φ75x12.5
Φ32x5.4	Φ90x15
Φ40x6.7	Φ110x18.3
Φ50x8.4	Φ125x20.8

PN 20 GLASS -FIBER PP-R PIPE

Specification(mm):

Φ20x2.8	Φ63x8.6
Φ25x3.5	Φ75x10.1
Φ32x4.4	Φ90x12.3
Φ40x5.5	Φ110x15.1
Φ50x6.9	Φ125x17.4

PN25 GLASS-FIBER PP-R PIPE

Specification(mm):

Φ20x3.4	Φ63x10.5
Φ25x4.2	Φ75x12.5
Φ32x5.4	Φ90x15
Φ40x6.7	Φ110x18.3
Φ50x8.4	Φ125x20.8

PN 20 PP-R ALUMINIUM PP-R PIPE

Specification(mm):

Φ20x3.1	Φ40x5.0
Φ25x3.3	Φ50x5.5
Φ32x4.1	Φ63x7.0

PN25 PP-R ALUMINIUM PP-R PIPE

Specification(mm):

Φ20x3.4	Φ40x6.7
Φ25x4.2	Φ50x8.4
Φ32x5.4	Φ63x10.5

PN20 PPR-ALU-PPR PIPE WITH UV PROTECTION LAYER


Specification(mm):

Φ20x2.8	Φ40x5.5
Φ25x3.5	Φ50x6.9
Φ32x4.4	Φ63x8.6

PN25 PPR-ALU-PPR PIPE WITH UV PROTECTION LAYER

Specification(mm):

Φ20x3.4	Φ40x6.7
Φ25x4.2	Φ50x8.4
Φ32x5.4	Φ63x10.5



Elbow 90°



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	
Φ125	

SOCKET



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	
Φ125	

Tee



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	
Φ125	

REDUCER SOCKET



Specification(mm):	
Φ25/20	Φ75/20
Φ32/20	Φ75/25
Φ32/25	Φ75/32
Φ40/20	Φ75/40
Φ40/25	Φ75/50
Φ40/32	Φ75/63
Φ50/20	Φ90/50
Φ50/25	Φ90/63
Φ50/32	Φ90/75
Φ50/40	Φ110/63
Φ63/20	Φ110/75
Φ63/25	Φ110/90
Φ63/32	
Φ63/40	
Φ63/50	
Φ75/20	



REDUCER Tee

Specification(mm):	
Φ20x25x20	Φ50x40x50
Φ25x20x20	Φ63x20x63
Φ25x20x25	Φ63x25x63
Φ25x25x20	Φ63x32x63
Φ32x20x20	Φ63x40x63
Φ32x20x25	Φ63x50x63
Φ32x20x32	Φ75x20x75
Φ32x25x20	Φ75x25x75
Φ32x25x25	Φ75x32x75
Φ32x25x32	Φ75x40x75
Φ40x20x40	Φ75x50x75
Φ40x25x40	Φ75x63x75
Φ40x32x40	Φ90x50x90
Φ50x20x50	Φ90x63x90
Φ50x25x50	Φ110x50x110
Φ50x32x50	Φ110x63x110



REDUCER

Specification(mm):	
Φ25/20	
Φ32/20	
Φ32/25	
Φ40/20	
Φ40/25	
Φ40/32	
Φ50/25	
Φ50/32	
Φ50/40	
Φ63/25	
Φ63/32	
Φ63/40	
Φ63/50	

Elbow 45°



Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	Φ125



Short crooked bend-1

Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	



Cross

Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	

Tail Elbow 90°



Specification(mm):	
Φ20	
Φ25	
Φ32	



Reducing Elbow

Specification(mm):	
Φ25/20	
Φ32/20	
Φ32/25	



Long crooked bend

Specification(mm):	
Φ20	
Φ25	
Φ32	

astic Union



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	



Union

Specification(mm):	
Φ20x1/2"	
Φ25x3/4"	
Φ32x1"	



TANK CONNECT

Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	





Stop end

Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	Φ125



Thread female plug

Specification(mm):	
Φ20x1/2"	
Φ25x3/4"	
Φ32x1"	



Thread plug-1

Specification(mm):	
1/2"	
3/4"	
1"	



Long thread plug

Specification(mm):	
1/2"	
3/4"	



clip

Specification(mm):	
Φ16	Φ25
Φ18	Φ32
Φ20	Φ40



clip

Specification(mm):	
Φ16	Φ32
Φ18	Φ40
Φ20	Φ50
Φ25	



Double clip

Specification(mm):	
Φ16	
Φ20	
Φ25	
Φ32	



Flange adaptor

Specification(mm):	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	






Flange

Specification(mm):	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	



Ruler

Specification(mm):	
Φ1/2"	





Female Thread Socket

Specification(mm):	
Φ20x1/2"	Φ32x1"
Φ20x3/4"	Φ32x11/4"
Φ25x1/2"	Φ40x1"
Φ25x3/4"	Φ40x11/4"
Φ25x1"	Φ50x11/2"
Φ32x1/2"	Φ63x2"
Φ32x3/4"	



Male Thread Socket

Specification(mm):	
Φ20x1/2"	Φ32x1"
Φ20x3/4"	Φ32x11/4"
Φ25x1/2"	Φ40x1"
Φ25x3/4"	Φ40x11/4"
Φ25x1"	Φ50x11/2"
Φ32x1/2"	Φ63x2"
Φ32x3/4"	



Female Thread Socket brass with seat

Specification(mm):	
Φ32x1"	Φ75x21/2"
Φ40x11/4"	Φ90x3"
Φ50x11/2"	Φ110x4"
Φ63x2"	



Male Thread Socket brass with seat

Specification(mm):	
Φ32x1"	Φ75x21/2"
Φ40x11/4"	Φ90x3"
Φ50x11/2"	Φ110x4"
Φ63x2"	



Female Thread elbow

Specification(mm):	
Φ20x1/2"	Φ32x1"
Φ20x3/4"	Φ32x11/4"
Φ25x1/2"	Φ40x1"
Φ25x3/4"	Φ40x11/4"
Φ25x1"	Φ50x11/2"
Φ32x1/2"	Φ63x2"
Φ32x3/4"	



Male Thread elbow

Specification(mm):	
Φ20x1/2"	Φ32x1"
Φ20x3/4"	Φ32x11/4"
Φ25x1/2"	Φ40x1"
Φ25x3/4"	Φ40x11/4"
Φ25x1"	Φ50x11/2"
Φ32x1/2"	Φ63x2"
Φ32x3/4"	



Female Thread Tee

Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x11/4"
Φ25x3/4"	Φ50x11/2"
Φ32x1/2"	Φ63x2"



Male Thread Tee

Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x11/4"
Φ25x3/4"	Φ50x11/2"
Φ32x1/2"	Φ63x2"



Check valve

Specification(mm):
Φ20
Φ25
Φ32



Female Seated Elbow

Specification(mm):	
Φ20x1/2"	
Φ20x3/4"	
Φ25x1/2"	
Φ25x3/4"	
Φ32x1"	



Male Seated Elbow

Specification(mm):	
Φ20x1/2"	
Φ20x3/4"	
Φ25x1/2"	
Φ25x3/4"	
Φ32x1"	



Check valve

Specification(mm):
Φ20
Φ25
Φ32



Double Elbow

Specification(mm):	
Φ20x1/2"	
Φ25x1/2"	



Double Elbow

Specification(mm):	
Φ20x1/2"	
Φ25x1/2"	



exchange hot&cold water

Specification(mm):	
Φ20x1/2"	
Φ25x1/2"	



Female Thread Iron ocke

Specification(mm):	
Φ20x1/2"	Φ40x11/4"
Φ20x3/4"	Φ50x11/2"
Φ25x3/4"	Φ63x2"
Φ25x1"	Φ75x21/2"
Φ32x3/4"	Φ90x3"
Φ32x1"	Φ110x4"




Male Thread Iron ocke

Specification(mm):	
Φ20x1/2"	Φ40x11/4"
Φ20x3/4"	Φ50x11/2"
Φ25x3/4"	Φ63x2"
Φ25x1"	Φ75x21/2"
Φ32x3/4"	Φ90x3"
Φ32x1"	Φ110x4"



Brass Double-nion

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63





Plastic Ball Valve

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63



Stainless Ball Valve

Specification(mm):		
Φ20	Φ50	Φ110
Φ25	Φ63	
Φ32	Φ75	
Φ40	Φ90	



IFAN PPR Plastic Union Ball Valve Brass Core

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63



ball valve with double union

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63



Female Ball Valve With Single Union

Specification(mm):
Φ20
Φ25
Φ32



Brass ball valve

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63



Male Brass ball valve

Specification(mm):
Φ20x1/2"
Φ25x3/4"
Φ32x1"



Female Brass ball valve

Specification(mm):
Φ20x1/2"
Φ25x3/4"
Φ32x1"



Female Ball Valve

Specification(mm):
Φ20x1/2"
Φ25x1/2"
Φ25x3/4"
Φ32x1"



Female Ball Valve

Specification(mm):
Φ20x1/2"
Φ25x1/2"
Φ25x3/4"
Φ32x1"



Female Ball Valve

Specification(mm):
Φ20x1/2"
Φ25x3/4"
Φ32x1"



Gate Valve

Specification(mm):		
Φ20	Φ40	Φ75
Φ25	Φ50	Φ90
Φ32	Φ63	Φ110



America Stop valve

Specification(mm):
Φ20
Φ25
Φ32



America Stop valve

Specification(mm):
Φ20
Φ25
Φ32



America Stop valve new design

Specification(mm):
Φ20
Φ25
Φ32



America Stop valve new design(Ball)

Specification(mm):
Φ20
Φ25
Φ32



Brass Valve - MINI

Specification(mm):
Φ20
Φ25
Φ32



Manifolds-1

Specification(mm):	
2 Ways	6 Ways
3 Ways	7 Ways
4 Ways	8 Ways
5 Ways	



Manifolds-2 With Female

Specification(mm):	
2 Ways	6 Ways
3 Ways	7 Ways
4 Ways	8 Ways
5 Ways	




Plug With Air Valve

Specification(mm):
Φ25
Φ32
Φ40



Cap

Specification(mm):
Φ25
Φ32
Φ40





Shelf

Specification(mm):	
Φ25	
Φ32	
Φ40	



Connection IFAN PPR to PEX IFAN

Specification(mm):	
Φ20x16(PE-X)	
Φ20x20(PE-X)	



Socket With Nut

Specification(mm):	
Φ20x1/2"	Φ25x1"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ32x11/4"
Φ25x3/4"	



Elbow With Nut

Specification(mm):	
Φ20x1/2"	Φ25x1"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ32x11/4"
Φ25x3/4"	



Tee With Nut

Specification(mm):	
Φ20x1/2"	Φ25x1"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ32x11/4"
Φ25x3/4"	



Radiator Valve Straight

Specification(mm):	
Φ20x1/2"	



Radiator Valve Elbow

Specification(mm):	
Φ20x1/2"	
Φ20x3/4"	
Φ25x1/2"	
Φ25x3/4"	



Radiator Valve Elbow

Specification(mm):	
Φ20x1/2"	
Φ20x3/4"	
Φ25x1/2"	
Φ25x3/4"	



Filter

Specification(mm):	
Φ20	Φ40
Φ25	Φ50
Φ32	Φ63



Female tee

Specification(mm):	
Φ50x3/4"	
Φ63x3/4"	



Female cross

Specification(mm):	
Φ32x3/4"	Φ50x3/4"
Φ40x3/4"	Φ63x3/4"



Manifold

Specification(mm):	
Φ50x3/4"	



Ppr Bibcock

Specification(mm):	
1/2"	
3/4"	



Ppr Angel Valve

Specification(mm):	
1/2"	
3/4"	



PPR hot machine

Specification(mm):	
Φ20-32	
Φ20-63	




Peeling tool

Specification(mm):	
Φ20x25	Φ75x90
Φ32x40	Φ90x110
Φ50x63	



Metal clamp Triphow

Specification(mm):		
Φ20	Φ50	Φ100
Φ25	Φ63	Φ125
Φ32	Φ75	Φ160
Φ40	Φ90	







HDPE PIPE & PE COMPRESSION FITTINGS

KESAN PE PIPES AND FITTINGS ARE AVAILABLE IN VAST RANGE WHATEVER MAY BE YOUR APPLICATION.

WE HAVE THE PE PIPING SYSTEM, RANGE OF PIPE SIZES IN VARIOUS THERMO PLASTICS, STARTS FROM 20MMTS TO 500MMTS DIA THAT CAN BE INSTALLED ON SURFACE, BURIED SLIP LINED, FLOATING OR SUBMERGED.

FLUIDS TRANSPORTED INCLUDE WATER, WASTE WATER, CHEMICALS AND HAZARDOUS WASTES.



PE Pipe PN-16 S11




Specification(mm):
Φ20x2.3
Φ25x2.3
Φ32x3.0
Φ40x3.7
Φ50x4.6
Φ63x5.8
Φ75x6.8
Φ90x8.2
Φ110x10.0
Φ125x11.4
Φ140x12.7
Φ160x14.6
Φ180x16.4
Φ200x18.2
Φ225x20.5
Φ250x22.7
Φ280x25.4
Φ315x28.6
Φ355x32.2
Φ400x36.3
Φ450x40.9
Φ500x45.4

PE Pipe PN-12.5 S13.6



Specification(mm):
Φ63x4.7
Φ75x5.6
Φ90x6.7
Φ110x8.1
Φ125x9.2
Φ140x10.3
Φ160x11.8
Φ180x13.3
Φ200x14.7
Φ225x16.6
Φ250x18.4
Φ280x20.6
Φ315x23.2
Φ355x26.1
Φ400x29.4
Φ450x33.1
Φ500x36.8

PE Pipe PN-10 S17



Specification(mm):
Φ75x4.5
Φ90x5.4
Φ110x6.6
Φ125x7.4
Φ140x8.3
Φ160x9.5
Φ180x10.7
Φ200x11.9
Φ225x13.4
Φ250x14.8
Φ280x16.6
Φ315x18.1
Φ355x21.1
Φ400x23.7
Φ450x26.7
Φ500x29.7

PE Pipe PN-10 S17




Specification(mm):
Φ110x5.3
Φ125x6.0
Φ140x6.7
Φ160x7.7
Φ180x8.6
Φ200x9.6
Φ225x10.8
Φ250x11.9
Φ280x13.4
Φ315x15.0
Φ355x16.9
Φ400x19.1
Φ450x21.5
Φ500x23.9

PE Pipe PN-06 S26



Specification(mm):
Φ110x4.2
Φ125x4.8
Φ140x5.4
Φ160x6.2
Φ180x6.9
Φ200x7.7
Φ225x8.6
Φ250x9.6
Φ280x10.7
Φ315x12.1
Φ355x13.6
Φ400x15.3
Φ450x17.2
Φ500x19.1



Socket



Specification(mm):	
Φ20	Φ75
Φ25	Φ90
Φ32	Φ110
Φ40	
Φ50	
Φ63	

Reduce socket



Specification(mm):		
Φ25x20	Φ50x25	Φ75x50
Φ32x20	Φ50x32	Φ75x63
Φ32x25	Φ50x40	Φ90x63
Φ40x20	Φ63x32	Φ90x75
Φ40x25	Φ63x40	Φ110x75
Φ40x32	Φ63x50	Φ110x90

Female socket



Specification(mm):	
Φ20x1/2"	
Φ32x3/4"	
Φ32x1"	
Φ40x1-1/4"	
Φ50x1-1/2"	
Φ63x2"	

Male Socket



Specification(mm):		
Φ20x1/2"	Φ25x1-1/2"	Φ50x1-1/2"
Φ20x3/4"	Φ32x1/2"	Φ50x2"
Φ20x1"	Φ32x3/4"	Φ63x2"
Φ25x1/2"	Φ32x1"	Φ75x2-1/2"
Φ25x3/4"	Φ32x1-1/4"	Φ90x3"
Φ25x1"	Φ32x1-1/2"	Φ110x4"
Φ25x1-1/4"	Φ25x1-1/4"	



Elbow Coude

Specification(mm):	
Φ20	Φ90
Φ25	Φ110
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	



Female Elbow

Specification(mm):	
Φ20x1/2"	
Φ20x3/4"	
Φ25x3/4"	
Φ32x1"	
Φ40x1-1/4"	
Φ50x1-1/2"	
Φ63x2"	

Male Elbow About Male



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1/2"	Φ63x2"



TEE T

Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	



Reduce Tee T-reduit

Specification(mm):	
Φ25x20x25	Φ50x32x50
Φ32x20x32	Φ50x40x50
Φ32x25x32	Φ63x25x63
Φ40x25x40	Φ63x32x63
Φ40x32x40	Φ63x40x63
Φ50x25x50	Φ63x50x63

Female Tee



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1/2"	Φ63x2"



Male Tee

Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1/2"	Φ63x2"



Cap About femelle

Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	

MALE SOCKET



Specification(mm):	
Φ20x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1"	Φ63x2"



FEMALE SOCKET

Specification(mm):	
Φ20x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1"	Φ63x2"



MALE ELBOW

Specification(mm):	
Φ20x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1"	Φ63x2"



PP TOOLS



Specification(mm):	
Φ40	
Φ50	
Φ63	



PP TOOLS

Specification(mm):	
Φ75	
Φ90	
Φ110	



FEMALE ELBOW

Specification(mm):	
Φ20x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ32x1"	Φ63x2"

EQUAL VALVE



Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	





MALE VALVE

Specification(mm):	
Φ20x1/2"	Φ63x2"
Φ25x3/4"	Φ75x2-1/2"
Φ32x1"	Φ90x3"
Φ40x1-1/4"	Φ110x4"
Φ50x1-1/2"	



FEMALE VALVE

Specification(mm):	
Φ20x1/2"	Φ63x2"
Φ25x3/4"	Φ75x2-1/2"
Φ32x1"	Φ90x3"
Φ40x1-1/4"	Φ110x4"
Φ50x1-1/2"	



Socket



Specification(mm):	
Φ20	Φ75
Φ25	Φ90
Φ32	Φ110
Φ40	
Φ50	
Φ63	

Reduce Socket



Specification(mm):	
Φ25X20	Φ50X25
Φ32X20	Φ50X32
Φ32X25	Φ50X40
Φ40X20	Φ63X32
Φ40X25	Φ63X40
Φ40X32	Φ63X50

Female Socket



Specification(mm):	
Φ20x1/2"	Φ40x1-1/4"
Φ25x1/2"	Φ50x1-1/2"
Φ25x3/4"	Φ63x2"
S32x1/2"	Φ75x2-1/2"
Φ32x3/4"	Φ90x3"
Φ32x1"	Φ110x4"

Male Socket



Specification(mm):	
Φ20x1/2"	Φ32x1"
Φ20x3/4"	Φ32x1-1/4"
Φ20x1"	Φ32x1-1/2"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ25x1"	Φ50x2"
Φ25x1-1/4"	Φ63x2"
Φ25x1-1/2"	Φ75x2-1/2"
Φ32x1/2"	Φ90x3"
Φ32x3/4"	Φ110x4"

Elbow



Specification(mm):
Φ20
Φ25
Φ32
Φ40
Φ50
Φ63
Φ75
Φ90
Φ110

Female Elbow



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ25x1"	Φ63x2"
Φ32x1/2"	

Male Elbow / Coude male



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ20x3/4"	Φ32x1"
Φ25x1/2"	Φ40x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ25x1"	Φ63x2"
Φ32x1/2"	

TEE T



Specification(mm):	
Φ20	Φ75
Φ25	Φ90
Φ32	Φ110
Φ40	
Φ50	
Φ63	

Reduce Tee T-reduit



Specification(mm):	
Φ25x20x25	
Φ32x20x32	
Φ32x25x32	
Φ40x25x40	
Φ40x32x40	
Φ50x40x50	
Φ63x50x63	

Female Tee / TE-femelle



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ25x1/2"	Φ32x1"
Φ25x3/4"	Φ40x1-1/4"
Φ25x1"	Φ50x1-1/2"
Φ32x1/2"	Φ63x2"

Male Tee / TE-Male



Specification(mm):	
Φ20x1/2"	Φ32x3/4"
Φ25x1/2"	Φ32x1"
Φ25x3/4"	Φ40x1-1/4"
Φ25x1"	Φ50x1-1/2"
Φ32x1/2"	Φ63x2"

Cap / About



Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	

Compression Ball Valve anne panaflexe



Specification(mm):	
Φ20	Φ63
Φ25	Φ75
Φ32	Φ90
Φ40	Φ110
Φ50	

Compression Ball Valve anne panaflexe male




Specification(mm):	
Φ20x1/2"	Φ63x2"
Φ25x3/4"	Φ75x2-1/2"
Φ32x1"	Φ90x3"
Φ40x1-1/4"	Φ110x4"
Φ50x1-1/2"	

Compression Female Valve Vanne panaflexe



Specification(mm):	
Φ20x1/2"	Φ63x2"
Φ25x3/4"	Φ75x2-1/2"
Φ32x1"	Φ90x3"
Φ40x1-1/4"	Φ110x4"
Φ50x1-1/2"	



Socket / Manchon



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	

Reduce Socket / Manchon Réduit



Specification(mm):	
Φ25x20	
Φ32x25	
Φ40x32	
Φ50x40	
Φ63x50	
Φ75x63	
Φ90x75	
Φ110x90	

Female Socket / Manchon femelle



Specification(mm):	
Φ20x1/2"	Φ40x1-1/2"
Φ20x3/4"	Φ50x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ25x1"	Φ63x1-1/2"
Φ32x3/4"	Φ63x2"
Φ32x1"	Φ75x2-1/2"
Φ32x1-1/4"	Φ90x3"
Φ40x1"	Φ110x4"
Φ40x1-1/4"	

Male Socket / Manchon femelle



Specification(mm):	
Φ20x1/2"	Φ40x1-1/2"
Φ20x3/4"	Φ50x1-1/4"
Φ25x3/4"	Φ50x1-1/2"
Φ25x1"	Φ63x1-1/2"
Φ32x3/4"	Φ63x2"
Φ32x1"	Φ75x2-1/2"
Φ32x1-1/4"	Φ90x3"
Φ40x1"	Φ110x4"
Φ40x1-1/4"	

Elbow / Coude



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	

Female Elbow / Coude Femelle



Specification(mm):	
L20x1/2"F	
L25x3/4"F	
L32x1"F	
L40x1-1/4"F	
L50x1-1/2"F	
L63x2"F	
L75x2-1/2"F	
L90x3"F	
L110x4"F	

Male Elbow / Coude male



Specification(mm):	
L20x1/2"M	
L25x3/4"M	
L32x1"M	
L40x1-1/4"M	
L50x1-1/2"M	
L63x2"M	
L75x2-1/2"M	
L90x3"M	
L110x4"M	

TEE T



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	

Reduce Tee T-reduit



Specification(mm):	
T25x20x25	
T32x25x32	
T40x32x40	
T50x40x50	
T63x50x63	
T75x63x75	
T90x75x90	
T110x90x110	

Female Tee / TE-femelle



Specification(mm):	
T20x1/2"F	T40x2"F
T25x1/2"F	T50x1-1/4"F
T25x3/4"F	T50x1-1/2"F
T32x3/4"F	T50x2"F
T32x1"F	T63x2"F
T32x1-1/4"F	T75x2-1/2"F
T40x1"F	T90x3"F
T40x1-1/4"F	T110x4"F
T40x1-1/2"F	

Male Tee / TE-Male



Specification(mm):	
T20x1/2"M	T40x2"M
T25x1/2"M	T50x1-1/4"M
T25x3/4"M	T50x1-1/2"M
T32x3/4"M	T50x2"M
T32x1"M	T63x2"M
T32x1-1/4"M	T75x2-1/2"M
T40x1"M	T90x3"M
T40x1-1/4"M	T110x4"M
T40x1-1/2"M	

Cap / Ambout



Specification(mm):	
Φ20	
Φ25	
Φ32	
Φ40	
Φ50	
Φ63	
Φ75	
Φ90	
Φ110	





MULTI-LAYER PIPES & FITTINGS

Size: 16, 18, 20, 25, 26, 32mm
PEX PIPES Size: 20mm-160mm
Pressure: PN16

Applications: Drinking Water
Cold & Hot
Color Available: All Customizable,
Such as Green, White, Grey, Blue

Pipes size range:



80003

PEXb-AL Stabi

Size(MM)	PACKING
16.2x2.6	100m/200m/500m
20x2.9	100m/200m
25x3.7	100m/50m
32x4.7	100m/50m
40x6.0	100m/50m



80004

PEXa pipes

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m

Pipes size range:



80005

PEXb

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m



80006

PEXb-EVOH

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m

Pipes size range:



80007

PEX-AL-PEX

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/100m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m



80008

PEXc-EVOH

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m

Pipes size range:



80009

PERT

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m



80010

PERT-EVOH

Size(MM)	PACKING
16x2.0	100m/200m/500m
16x2.2	100m/200m/500m
20x2.0	100m/200m/300m
20x2.8	100m/200m
25x3.5	100m/50m
32x4.4	100m/50m



PEX PIPE FITTINGS

Size: 16, 18, 20, 25, 26, 32mm
PEX PIPES Size: 20mm-160mm
Pressure: PN16

**Applications: Drinking Water
Cold & Hot**
**Color Available: All Customizable,
Such as Green, White, Grey, Blue**

